

ANACONDA

WALL/SURFACE/RECESSED

TO ACCOMPANY ANACONDA SPECIFICATION SHEET



Code	Cutout size	Fixing Detail	IP Rating Front / Rear	MacAdam (SDCM)	Power Factor	No. of drivers	Inrush Current (per driver)	Nominal Weight (Kg)	Rated Life	Mains Voltage (V)	Mains Frequency (Hz)
ANA/NM/3W/MT/SUR	N/A	"2 @ 115mm (ceiling)	IP20	N/A	N/A	1	N/A	2.5Kg	50,000 hrs	220-240	50-60
ANA/NM/3W/DST/SUR	N/A	"2 @ 115mm (ceiling)	IP20	N/A	N/A	1	N/A	2.5Kg	50,000 hrs	220-240	50-60
ANA/M/3W/MT/SUS	N/A	"2 @ 115mm (ceiling)	IP20	N/A	N/A	1	N/A	2.5Kg	50,000 hrs	220-240	50-60
ANA/M/3W/DST/SUS	N/A	"2 @ 115mm (ceiling)	IP20	N/A	N/A	1	N/A	2.5Kg	50,000 hrs	220-240	50-60



Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25 °C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/- 10%. Synergy reserve the right to amend or change details without prior notification.

REVISED :22 August 2022