

AXIOME SURFACE

SURFACE LED DOWNLIGHT

TO ACCOMPANY AXIOME SURFACE SPECIFICATION SHEET



Code	Cutout size	Fixing Detail	IP Rating Front / Rear	MacAdam (SDCM)	Power Factor	No. of drivers	Inrush Current (per driver)	Nominal Weight (Kg)	Rated Life	Mains Voltage (V)	Mains Frequency (Hz)
AXMW/F/1500/3K8/SM	N/A	Central BESA	IP20 / IP20	6	0.53	1	15A / 100uS	0.61	50,000 L70/B50	220-240	50-60
AXMW/F/1500/4K8/SM	N/A	Central BESA	IP20 / IP20	6	0.53	1	15A / 100uS	0.61	50,000 L70/B50	220-240	50-60
AXMW/F/2300/3K8/SM	N/A	Central BESA	IP20 / IP20	6	0.53	1	15A / 100uS	0.61	50,000 L70/B50	220-240	50-60
AXMW/F/2300/4K8/SM	N/A	Central BESA	IP20 / IP20	6	0.53	1	15A / 100uS	0.61	50,000 L70/B50	220-240	50-60



Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25 °C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/- 10%. Synergy reserve the right to amend or change details without prior notification.

REVISED :25 July 2022