

BLOK

RECESSED EMERGENCY EXIT SIGN

TO ACCOMPANY BLOK SPECIFICATION SHEET



Code	Cutout size (mm)	Fixing Detail	IP Rating Front / Rear	MacAdam (SDCM)	Power Factor	No. of drivers	Inrush Current (per driver)	Nominal Weight (Kg)	Rated Life	Mains Voltage (V)	Mains Frequency (Hz)
BLKW/M/3W/MT/EC/**	335x95	N/A	IP20	N/A	N/A	1	N/A	3Kg	50,000hrs	230	50
BLKW/M/3W/DST/EC/**	335x95	N/A	IP20	N/A	N/A	1	N/A	3Kg	50,000hrs	230	50
BLKW/M/3W/MT/ISO/**	335x95	N/A	IP20	N/A	N/A	1	N/A	3Kg	50,000hrs	230	50
BLKW/M/3W/DST/ISO/**	335x95	N/A	IP20	N/A	N/A	1	N/A	3Kg	50,000hrs	230	50



Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25 °C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/- 10%. Synergy reserve the right to amend or change details without prior notification.

REVISED :22 August 2022