

CANNE

SURFACE LED DOWNLIGHT

TO ACCOMPANY CANNE SPECIFICATION SHEETS



| Code | Cutout size | Fixing Detail | IP Rating Front / Rear | MacAdam (SDCM) | Power Factor | No. of drivers | Inrush Current (per driver) | Nominal Weight (Kg) | Rated Life | Mains Voltage (V) | Mains Frequency (Hz) |
|-----------------|-------------|--------------------|------------------------|----------------|--------------|----------------|-----------------------------|---------------------|--------------------|-------------------|----------------------|
| CANW/F/1100/3K8 | N/A | 3-off on 150mm PCD | IP20 / IP20 | 3 | >0.9 | 1 | 14A / 240uS | 3 | >60,000hrs L70/B10 | 220-240 | 50-60 Hz |
| CANW/F/1100/4K8 | N/A | 3-off on 150mm PCD | IP20 / IP20 | 3 | >0.9 | 1 | 14A / 240uS | 3 | >60,000hrs L70/B10 | 220-240 | 50-60 Hz |
| CANW/F/2000/3K8 | N/A | 3-off on 150mm PCD | IP20 / IP20 | 3 | >0.9 | 1 | 14.5A / 220uS | 3 | >60,000hrs L70/B10 | 220-240 | 50-60 Hz |
| CANW/F/2000/4K8 | N/A | 3-off on 150mm PCD | IP20 / IP20 | 3 | >0.9 | 1 | 14.5A / 220uS | 3 | >60,000hrs L70/B10 | 220-240 | 50-60 Hz |
| CANW/F/3000/3K8 | N/A | 3-off on 150mm PCD | IP20 / IP20 | 3 | >0.9 | 1 | 14.5A / 220uS | 3 | >60,000hrs L70/B10 | 220-240 | 50-60 Hz |
| CANW/F/3000/4K8 | N/A | 3-off on 150mm PCD | IP20 / IP20 | 3 | >0.9 | 1 | 14.5A / 220uS | 3 | >60,000hrs L70/B10 | 220-240 | 50-60 Hz |
| CANW/F/4000/3K8 | N/A | 3-off on 150mm PCD | IP20 / IP20 | 3 | >0.9 | 1 | 23.5A / 272uS | 3 | >60,000hrs L70/B10 | 220-240 | 50-60 Hz |
| CANW/F/4000/4K8 | N/A | 3-off on 150mm PCD | IP20 / IP20 | 3 | >0.9 | 1 | 23.5A / 272uS | 3 | >60,000hrs L70/B10 | 220-240 | 50-60 Hz |



Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25 °C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/- 10%. Synergy reserve the right to amend or change details without prior notification.

REVISED :25 July 2022 4:25