

# CORVUS

## LED CEILING BULKHEAD

TO ACCOMPANY CORVUS SPECIFICATION SHEET



Code	Cutout size	Fixing Detail	IP Rating Front / Rear	MacAdam (SDCM)	Power Factor	No. of drivers	Inrush Current (per driver)	Nominal Weight (Kg)	Rated Life	Mains Voltage (V)	Mains Frequency (Hz)
CVS/12/F/0450/4K8	110mm dia	N/A	IP44 / IP44	5	>0.6	1	30A / 304uS	0.28	36,000hrs L70 / B50	220-240	50-60
CVS/17/F/0900/4K8	160mm dia	N/A	IP44 / IP44	5	>0.6	1	30A / 304uS	0.32	36,000hrs L70 / B50	220-240	50-60
CVS/24/F/1800/4K8	225mm dia	N/A	IP44 / IP44	5	>0.6	1	30A / 304uS	0.6	36,000hrs L70 / B50	220-240	50-60



Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25 °C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/- 10%. Synergy reserve the right to amend or change details without prior notification.

REVISED :19 August 2022