


DISCUS

LED BULKHEAD

TO ACCOMPANY DISCUS SPECIFICATION SHEET



Code	Cutout size	Fixing Detail	IP Rating Front / Rear	MacAdam (SDCM)	Power Factor	No. of drivers	Inrush Current (per driver)	Nominal Weight (Kg)	Rated Life	Mains Voltage (V)	Mains Frequency (Hz)
DCS/F/2200/CB/4K8	N/A	BESA fixing & 2x side conduit entry	IP40	< 4	>0.9	1	< 16 A / 100uS	1.5	>58,000 hrs L80/B10	220-240	50-60
DCS/F/2000/WB/4K8	N/A	BESA fixing & 2x side conduit entry	IP40	< 4	>0.9	1	< 16 A / 100uS	1.5	>58,000 hrs L80/B10	220-240	50-60
DCS/F/3900/CB/4K8	N/A	BESA fixing & 2x side conduit entry	IP40	< 4	>0.9	1	< 16 A / 100uS	1.8	>58,000 hrs L80/B10	220-240	50-60
DCS/F/3500/WB/4K8	N/A	BESA fixing & 2x side conduit entry	IP40	< 4	>0.9	1	< 16 A / 100uS	1.8	>58,000 hrs L80/B10	220-240	50-60



Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25 °C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/- 10%. Synergy reserve the right to amend or change details without prior notification.

REVISED :22 August 2022