

ONYX

EMERGENCY BULKHEAD

TO ACCOMPANY ONYX SPECIFICATION SHEET



Code	Cutout size	Fixing Detail	IP Rating Front / Rear	MacAdam (SDCM)	Power Factor	No. of drivers	Inrush Current (per driver)	Nominal Weight (Kg)	Rated Life	Mains Voltage (V)	Mains Frequency (Hz)
ONX/NM/3W/MT	N/A	Central BESA	IP65	N/A	N/A	1	N/A	1.1Kg	50,000 hrs (LEDs & control gear)	220-240	50-60
ONX/NM/3W/DST	N/A	Central BESA	IP65	N/A	N/A	1	N/A	1.1Kg	50,000 hrs (LEDs & control gear)	220-240	50-60
ONX/M/3W/MT	N/A	Central BESA	IP65	N/A	N/A	1	N/A	1.1Kg	50,000 hrs (LEDs & control gear)	220-240	50-60
ONX/M/3W/DST	N/A	Central BESA	IP65	N/A	N/A	1	N/A	1.1Kg	50,000 hrs (LEDs & control gear)	220-240	50-60



Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25 °C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/- 10%. Synergy reserve the right to amend or change details without prior notification.

REVISED :22 August 2022 1