

POLARIS 1 BOX

SQUARE LINEAR PENDANT

TO ACCOMPANY POLARIS 1 BOX SPECIFICATION SHEET



| Code | Fixing Detail | IP Rating Front / Rear | MacAdam (SDCM) | Power Factor | No. of drivers | Inrush Current (per driver) | Nominal Weight (Kg) | Rated Life | Mains Voltage (V) | Mains Frequency (Hz) |
|---------------------|---------------|------------------------|----------------|--------------|----------------|-----------------------------|---------------------|-----------------------|-------------------|----------------------|
| P1BXB/OS/F/0640/4K8 | See Drawing | IP20/IP20 | 3 | >0.9 | 1 | 51.5A / 157uS | 5.7 | >72,000 hrs L80 / F10 | 220-240 | 50-60 |
| P1BXB/OS/F/0920/4K8 | See Drawing | IP20/IP20 | 3 | >0.9 | 1 | 51.5A / 157uS | 8.2 | >72,000 hrs L80 / F10 | 220-240 | 50-60 |
| P1BXB/OS/F/1200/4K8 | See Drawing | IP20/IP20 | 3 | >0.9 | 2 | 51.5A / 157uS | 10.9 | >72,000 hrs L80 / F10 | 220-240 | 50-60 |



Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25 °C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/- 10%. Synergy reserve the right to amend or change details without prior notification.

REVISED :20 July 2022