

POLARIS 1

SURFACE OR SUSPENDED LED LINEAR

TO ACCOMPANY POLARIS 1 SPECIFICATION SHEET



Code	Fixing Detail	IP Rating Front / Rear	MacAdam (SDCM)	Power Factor	No. of drivers	Inrush Current (per driver)	Nominal Weight (Kg)	Rated Life	Mains Voltage (V)	Mains Frequency (Hz)
P11B/OS/F/0600/4K8	2 - 65mm from ends	IP20/IP20	3	>0.9	1	21A / 126uS	2	>72,000 hrs L80 / F10	220-240	50-60
P11B/OS/F/0885/4K8	2 - 65mm from ends	IP20/IP20	3	>0.9	1	5.5A / 20uS	2.7	>72,000 hrs L80 / F10	220-240	50-60
P11B/OS/F/1165/4K8	2 - 65mm from ends	IP20/IP20	3	>0.9	1	5.5A / 20uS	3.3	>72,000 hrs L80 / F10	220-240	50-60
P11B/OS/F/1450/4K8	2 - 65mm from ends	IP20/IP20	3	>0.9	1	25A / 280uS	3.8	>72,000 hrs L80 / F10	220-240	50-60
P11B/OS/F/1730/4K8	2 - 65mm from ends	IP20/IP20	3	>0.9	1	25A / 280uS	4.4	>72,000 hrs L80 / F10	220-240	50-60
P11B/OS/F/2015/4K8	2 - 65mm from ends	IP20/IP20	3	>0.9	1	51.5A / 157uS	5.1	>72,000 hrs L80 / F10	220-240	50-60
P11B/OS/F/2295/4K8	2 - 65mm from ends	IP20/IP20	3	>0.9	1	51.5A / 157uS	5.7	>72,000 hrs L80 / F10	220-240	50-60
P11B/OS/F/2580/4K8	3 - 65mm from ends & one on centreline	IP20/IP20	3	>0.9	1	51.5A / 157uS	6.3	>72,000 hrs L80 / F10	220-240	50-60
P11B/OS/F/2860/4K8	3 - 65mm from ends & one on centreline	IP20/IP20	3	>0.9	1	51.5A / 157uS	6.9	>72,000 hrs L80 / F10	220-240	50-60
P11B/OS/F/3145/4K8	3 - 65mm from ends & one on centreline	IP20/IP20	3	>0.9	1	51.5A / 157uS	7.6	>72,000 hrs L80 / F10	220-240	50-60
P11B/OS/F/3425/4K8	3 - 65mm from ends & one on centreline	IP20/IP20	3	>0.9	1	51.5A / 157uS	8.2	>72,000 hrs L80 / F10	220-240	50-60
P11B/OS/F/3710/4K8	3 - 65mm from ends & one on centreline	IP20/IP20	3	>0.9	1	51.5A / 157uS	8.8	>72,000 hrs L80 / F10	220-240	50-60
P11B/OS/F/3990/4K8	4 - 65mm from ends & 2 650mm either side of centre	IP20/IP20	3	>0.9	2	51.5A / 157uS	9.7	>72,000 hrs L80 / F10	220-240	50-60
P11B/OS/F/4275/4K8	4 - 65mm from ends & 2 700mm either side of centre	IP20/IP20	3	>0.9	2	51.5A / 157uS	10.3	>72,000 hrs L80 / F10	220-240	50-60
P11B/OS/F/4555/4K8	4 - 65mm from ends & 2 735mm either side of centre	IP20/IP20	3	>0.9	2	51.5A / 157uS	10.9	>72,000 hrs L80 / F10	220-240	50-60



Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25 °C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/- 10%. Synergy reserve the right to amend or change details without prior notification.

REVISED :18 July 2022 8:39