

POLARIS 70



LINEAR WITH 5 LIGHT EMITTING SIDESILLUMINATED EXIT SIGN

TO ACCOMPANY POLARIS 70 SPECIFICATION SHEET

Code	Fixing Detail	IP Rating Front / Rear	MacAdam (SDCM)	Power Factor	No. of drivers	Inrush Current (per driver)	Nominal Weight (Kg)	Rated Life	Mains Voltage (V)	Mains Frequency (Hz)
P70/OS/F/0585/4K8	2 - 65mm from ends	IP20 / IP20	3	>0.9	1	10A / 100uS	1.4Kg	50,000hrs L80 / B20	220-240	50-60
P70/OS/F/0860/4K8	2 - 65mm from ends	IP20 / IP20	3	>0.9	1	10A / 100uS	2.1Kg	50,000hrs L80 / B20	220-240	50-60
P70/OS/F/1145/4K8	2 - 65mm from ends	IP20 / IP20	3	>0.9	1	10A / 100uS	2.6Kg	50,000hrs L80 / B20	220-240	50-60
P70/OS/F/1425/4K8	2 - 65mm from ends	IP20 / IP20	3	>0.9	1	10A / 100uS	3.1Kg	50,000hrs L80 / B20	220-240	50-60
P70/OS/F/1710/4K8	2 - 65mm from ends	IP20 / IP20	3	>0.9	2	10A / 100uS	3.8Kg	50,000hrs L80 / B20	220-240	50-60
P70/OS/F/2265/4K8	3 - 65mm from ends & one on centreline	IP20 / IP20	3	>0.9	2	10A / 100uS	5.2Kg	50,000hrs L80 / B20	220-240	50-60
P70/OS/F/2825/4K8	3 - 65mm from ends & one on centreline	IP20 / IP20	3	>0.9	2	10A / 100uS	6.6Kg	50,000hrs L80 / B20	220-240	50-60



Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25 °C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/- 10%. Synergy reserve the right to amend or change details without prior notification.

REVISED :20 July 2022