

# POLARIS N2

## LED LINEAR PENDANT TUBE

TO ACCOMPANY POLARIS N2 SPECIFICATION SHEET



Code	Fixing Detail	IP Rating Front / Rear	MacAdam (SDCM)	Power Factor	No. of drivers	Inrush Current (per driver)	Nominal Weight (Kg)	Rated Life	Mains Voltage (V)	Mains Frequency (Hz)
PN2G/OS/F/0645/4K8	2-off	IP68	3	0.95	1	25A / 250uS	1.4	>80,000 hrs L80/B10	220-240	50-60
PN2G/OS/F/0925/4K8	2-off	IP68	3	0.95	1	25A / 250uS	1.8	>80,000 hrs L80/B10	220-240	50-60
PN2G/OS/F/1205/4K8	2-off	IP68	3	0.95	1	25A / 250uS	2.33	>80,000 hrs L80/B10	220-240	50-60
PN2G/OS/F/1485/4K8	2-off	IP68	3	0.95	1	33A / 250uS	2.7	>80,000 hrs L80/B10	220-240	50-60
PN2G/OS/F/1765/4K8	2-off	IP68	3	0.95	1	33A / 250uS	3.01	>80,000 hrs L80/B10	220-240	50-60
PN2G/OS/F/2045/4K8	2-off	IP68	3	0.95	1	33A / 250uS	3.4	>80,000 hrs L80/B10	220-240	50-60



Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25 °C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/- 10%. Synergy reserve the right to amend or change details without prior notification.

REVISED :20 July 2022