

PRO SPOT

DALI TEST EMERGENCY LUMINAIRE

TO ACCOMPANY PRO SPOT SPECIFICATION SHEET



Code	Cut Out Size	IP Rating Front / Rear	MacAdam (SDCM)	Power Factor	No. of drivers	Inrush Current (per driver)	Nominal Weight (Kg)	Rated Life	Mains Voltage (V)	Mains Frequency (Hz)
PSEW/3W/DST/OA	42mm Dia	IP20	N/A	0.44	1	4.5A	0.38	50,000hrs (LEDs & Control Gear)	220-240	50-60
PSEW/3W/DST/COR	42mm Dia	IP20	N/A	0.44	1	4.5A	0.38	50,000hrs (LEDs & Control Gear)	220-240	50-60
PSEB/3W/DST/OA	42mm Dia	IP20	N/A	0.44	1	4.5A	0.38	50,000hrs (LEDs & Control Gear)	220-240	50-60
PSEB/3W/DST/COR	42mm Dia	IP20	N/A	0.44	1	4.5A	0.38	50,000hrs (LEDs & Control Gear)	220-240	50-60



Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25 °C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/- 10%. Synergy reserve the right to amend or change details without prior notification.

REVISED :22 August 2022