

SOMBRERO DISC

OPAL LED FEATURE PENDANT

TO ACCOMPANY SOMBRERO SPECIFICATION SHEET



Code	Fixing Centres	IP Rating Front / Rear	MacAdam (SDCM)	Power Factor	No. of drivers	Inrush Current (per driver)	Nominal Weight (Kg)	Rated Life	Mains Voltage (V)	Mains Frequency (Hz)
Suspended										
SOMDSB/OS/F/0340/4K8	See drawing	IP20 / IP20	3	>0.9	1	10A / 100 µs		50,000hrs L80 / B20	220-240	50-60
SOMDSB/OS/F/0440/4K8	See drawing	IP20 / IP20	3	>0.9	1	10A / 100 µs		50,000hrs L80 / B20	220-240	50-60
SOMDSB/OS/F/0540/4K8	See drawing	IP20 / IP20	3	>0.9	1	10A / 100 µs		50,000hrs L80 / B20	220-240	50-60
SOMDSB/OS/F/0820/4K8	See drawing	IP20 / IP20	3	>0.9	1	10A / 100 µs		50,000hrs L80 / B20	220-240	50-60
Ceiling Surface										
SOMDCB/OS/F/0340/4K8	See Drawing	IP20 / IP20	3	>0.9	1	10A / 100 µs		50,000hrs L80 / B20	220-240	50-60
SOMDCB/OS/F/0440/4K8	See Drawing	IP20 / IP20	3	>0.9	1	10A / 100 µs		50,000hrs L80 / B20	220-240	50-60
SOMDCB/OS/F/0540/4K8	See Drawing	IP20 / IP20	3	>0.9	1	20A / 100 µs		50,000hrs L80 / B20	220-240	50-60
SOMDCB/OS/F/0820/4K8	See Drawing	IP20 / IP20	3	>0.9	1	20A / 100 µs		50,000hrs L80 / B20	220-240	50-60
Recessed										
SOMDRB/OS/F/0340/4K8	381mm cut out	IP20 / IP20	3	>0.9	1	10A / 100 µs		50,000hrs L80 / B20	220-240	50-60
SOMDRB/OS/F/0440/4K8	456mm cut out	IP20 / IP20	3	>0.9	1	10A / 100 µs		50,000hrs L80 / B20	220-240	50-60
SOMDRB/OS/F/0540/4K8	596mm cut out	IP20 / IP20	3	>0.9	1	20A / 100 µs		50,000hrs L80 / B20	220-240	50-60
SOMDRB/OS/F/0820/4K8	876mm cut out	IP20 / IP20	3	>0.9	1	20A / 100 µs		50,000hrs L80 / B20	220-240	50-60

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25 °C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/- 10%. Synergy reserve the right to amend or change details without prior notification.

REVISED :22 July 2022

