

SOMBRERO DISC WALL

WALL MOUNTED LED FEATURE DISC

TO ACCOMPANY SOMBRERO WALL OPAL AND LOW GLARE SPECIFICATION SHEETS



Code	Fixing Centres	IP Rating Front / Rear	MacAdam (SDCM)	Power Factor	No. of drivers	Inrush Current (per driver)	Nominal Weight (Kg)	Rated Life	Mains Voltage (V)	Mains Frequency (Hz)
SOMDWB/OS/F/0380/4K8	See Drawing	IP20 / IP20	3	>0.9	1	10A / 100 μ s		50,000hrs L80 / B20	220-240	50-60
SOMDWB/OS/F/0455/4K8	See Drawing	IP20 / IP20	3	>0.9	1	10A / 100 μ s		50,000hrs L80 / B20	220-240	50-60
SOMDWB/HX/F/0380/4K8	See Drawing	IP20 / IP20	3	>0.9	1	10A / 100 μ s		50,000hrs L80 / B20	220-240	50-60
SOMDWB/HX/F/0455/4K8	See Drawing	IP20 / IP20	3	>0.9	1	10A / 100 μ s		50,000hrs L80 / B20	220-240	50-60



Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25 °C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/- 10%. Synergy reserve the right to amend or change details without prior notification.

REVISED :13 October 2021