
# STAND OUT FROM THE CROWD











#### SPECIFICATION DATA

Code	Weight	Size (mm)	Luminaire power (tcW)	Delivered Lumens (Llm)	Efficacy (llm/cw)	Colour Temp (°K)	CRI	Power Factor (TOP driver)
P1HB/OS/F/0280/4K8	8.1	6x280mm	47	5510	117.2	4000K	>80	0.95
P1HB/OS/F/0580/4K8	9.7	6x580mm	94	11020	117.2	4000K	>80	0.95
P1HB/OS/F/0880/4K8	11.2	6x880mm	140	16530	118.1	4000K	>80	0.95
P1HB/OS/F/1160/4K8	14.6	6x1160mm	187	22040	117.9	4000K	>80	0.95
P1HB/HX/F/0280/4K8	8.1	6x280mm	47	4240	90.2	4000K	>80	0.95
P1HB/HX/F/0580/4K8	9.7	6x580mm	94	8480	90.2	4000K	>80	0.95
P1HB/HX/F/0880/4K8	11.2	6x880mm	140	12720	90.9	4000K	>80	0.95
P1HB/HX/F/1160/4K8	14.6	6x1160mm	187	16960	90.7	4000K	>80	0.95

5 year warranty

• See website for LDT files

• MacAdam 3 Step

• Rated Life (hrs) : >60,000

• IP20





### **Polaris 1 Hexagon Linear LED Feature Pendant**



#### Construction

- Extruded aluminium profile
- Clip-in diffuser
- European brand control gear
- Made in the UK

#### **Features**

- High efficiency LED boards
- Range of length options
- Wide-beam light distribution

#### **Applications**

- Commercial and Business Areas
- Public buildings
- Housing
- Offices
- Hotels and Restaurants
- Arts and Culture spaces

#### **Benefits**

- Custom-fit options
- Contemporary style
- Energy efficient solution
- 5 Year warranty

#### **Optical Options**

Code	Description	
/OS	Opal	
/HXP	Low Glare	

#### **CCT Options**

Code	Description	
4K8	4000K (Standard)	
3K8	3000K	


For 3000K version, replace '4K8' in part number with '3K8'

#### **Control Options**

Code	Description	
D	DALI	
S	Switchdim control	

For DALI control, replace 'F' in part number with 'D' for SwitchDim replace 'F' with 'S'

#### **Dimensions**



#### **Mounting Options**

Code	Description	
P1/SUS/1.25M	Suspended 1.25M	
P1/SUS/3.0M	Suspended 3M	
P1/SUS/5.0M	Suspended 5M	
	Surface Mounted (Standard)	
For suspended specify the codes as required		

ended specify the codes as require

#### **Finish Options**

Code	Description	
В	Black RAL 9005 (Standard)	
W	White RAL 9016	
S	Silver RAL 9006	
RAL	Any RAL by request	
SFX	Special effect finishes (SFX) by request. See Product Portfolio	

For White finish, replace 'B' in part number with 'W' for Silver replace 'B' with 'S'. Contact us for custom RAL and SFX finish prices

#### **Emergency Options**

Code	Description	
/EM	3 hour maintained, manual test	
/ED	3 hour maintained, DALI / Self Test	

For emergency version, add onto end of part number as required


#### **Continuous Options**

Code	Description
С	Continuous
S	Start of run
E	End of run

Part numbers are for individual luminaires. For continuous replace 'l' in part number with 'C', 'S' or 'E'. Please sepcify continuous seperately. ie P1CB/OS/F/3990/4K8

Please note, The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person.






## Polaris 1 Hexagon


Linear LED Feature Pendant








#### **STANDARD FINISHES**




Black finish as standard - respresented by 'B' in the part number


#### **ANY RAL BY REQUEST**



For White finish, replace 'B' in part number with 'W'



For Silver finish, replace 'B' in part number with 'S'



Contact us for custom RAL finishes prices and specification. Synergy Creativ can powder coat fittings to any RAL colour you require by request.


#### **SPECIAL FX FINISHES**



Contact us for all SFX finish prices and specification. Synergy Creativ's Special FX tetxured finished included Marble, Concrete, Wood Grains, Metallic and many more. all images are for illustrative purposes only actual product may vary, please contact us for samples.









HEADOFFICE: Unit 5, Trident industrial Estate, Pindar Rd, Hoddesdon Hertfordshire, EN11 0WZ SHOWROOM: 121 - 131 Rosebery Ave, London, EC1R 4RF SHOWROOM: 1 New York St, Manchester, M1 4HD



EnabLED Licensing Program for LED Luminaires and Retrofit Bulbs

ACTION Mary Commencial Refing Contract



01992 445828