



SYNERGY
CREATIV.

**STAND OUT FROM
THE CROWD**

Feature Pendant

Sombrero Ring Low Glare

SVELTO



SPECIFICATION DATA

Code	Finish	Size (mm)	Delivered Lumens (lm)	Total System Wattage (W)	Efficacy (lm/cw)	Colour Temp (°K)	CRI
Suspended							
SOMRSB/HX/F/0700/4K8	Black	ø 700 x 70 x 80	3847	29	132.7	4000K	>80
SOMRSB/HX/F/0900/4K8	Black	ø 900 x 70 x 80	4946	37	133.7	4000K	>80
SOMRSB/HX/F/1220/4K8	Black	ø 1170 x 70 x 80	6595	50	131.9	4000K	>80
SOMRSB/HX/F/1500/4K8	Black	ø 1450 x 70 x 80	8793	66	133.2	4000K	>80
SOMRSB/HX/F/2000/4K8	Black	ø 1900 x 70 x 80	10992	82	134.0	4000K	>80
SOMRSB/HX/F/2500/4K8	Black	ø 2425 x 70 x 80	15694	118	133.0	4000K	>80
SOMRSB/HX/F/3000/4K8	Black	ø 3020 x 70 x 80	17587	132	133.2	4000K	>80
Surface							
SOMRCB/HX/F/0700/4K8	Black	ø 700 x 70 x 80	3847	29	132.7	4000K	>80
SOMRCB/HX/F/0900/4K8	Black	ø 900 x 70 x 80	4946	37	133.7	4000K	>80
SOMRCB/HX/F/1220/4K8	Black	ø 1170 x 70 x 80	6595	50	131.9	4000K	>80
SOMRCB/HX/F/1500/4K8	Black	ø 1450 x 70 x 80	8793	66	133.2	4000K	>80
SOMRCB/HX/F/2000/4K8	Black	ø 1900 x 70 x 80	10992	82	134.0	4000K	>80
SOMRCB/HX/F/2500/4K8	Black	ø 2425 x 70 x 80	15694	118	133.0	4000K	>80
SOMRCB/HX/F/3000/4K8	Black	ø 3020 x 70 x 80	17587	132	133.2	4000K	>80

- Part numbers are for individual luminaires.
- 5 year warranty
- See website for LDT files
- For CAD/BIM contact us
- For bespoke lengths please contact us
- See website for Technical Data Sheet
- IP20

Sombrero Ring Glare



Construction

- Extruded aluminium profile
- Die-cast aluminium end caps
- Clip-in diffuser
- Tridonic LED boards

Features

- High efficiency LED boards
- Range of length options
- Wide-beam light distribution

Applications

- Commercial and Business Areas
- Public buildings
- Housing
- Offices
- Hotels and Restaurants
- Arts and Culture spaces

Benefits

- Custom-fit options
- Contemporary style
- Energy efficient solution
- 5 Year warranty

Optical Options

Code	Description
OS	Opal
HX	Low Glare

CCT Options

Code	Description
4K8	4000K (Standard)
3K8	3000K

For 3000K version, replace '4K8' in part number with '3K8'

Control Options

Code	Description
D	DALI
S	Switchdim control

For DALI control, replace 'F' in part number with 'D' for SwitchDim replace 'F' with 'S'

Mounting Options

Code	Description
N/A	Suspended
N/A	Surface
N/A	Recessed

Finish Options

Code	Description
B	Black RAL 9005 (Standard)
W	White RAL 9016
S	Silver RAL 9006
RAL	Any RAL by request
SFX	Special effect finishes (SFX) by request. See Product Portfolio

For White finish, replace 'B' in part number with 'W' for Silver replace 'B' with 'S'. Contact us for custom RAL and SFX finish prices

Emergency Options

Code	Description
/EM	3 hour maintained, manual test
/ED	3 hour maintained, DALI / Self Test

For emergency version, add onto end of part number as required



HEAD OFFICE: Unit 4, Charlton Mead Lane, Hoddesdon, Hertfordshire EN11 0DJ
 SHOWROOM: 121-131 Rosebery Ave, London EC1R 4RF
 SHOWROOM: 1 New York St, Manchester M1 4HD

01992 445828

