

Discus

Bulkhead LED Luminaire



SPECIFICATION DATA

Code	Finish	Size (mm)	Delivered Lumens (lm)	Total System Wattage (W)	Efficacy (lm/cw)	Colour Temp (°K)	CRI
DCS/F/2200/CB/4K8	Clear base halo effect	435	2247	18	124.8	4000	>80
DCS/F/2000/WB/4K8	White base	435	2030	18	112.8	4000	>80
DCS/F/3900/CB/4K8	Clear base halo effect	470	3909	30	130.3	4000	>80
DCS/F/3500/WB/4K8	White base	470	3480	30	116.0	4000	>80

- 5 year warranty
- See website for LDT files
- For CAD/BIM contact us
- For bespoke lengths please contact us
- See website for Technical Data Sheet
- IP20



TRIDONIC



Scenario
INTELLIGENT INFRASTRUCTURES



Discus

Bulkhead LED Luminaire



Construction

- PMMA opal diffuser

Features

- Ceiling or wall fixtures
- Emergency versions
- Dimmable versions

Applications

- Offices
- Public spaces
- Hospitals
- Washrooms
- Hotels and restaurants
- Schools

Benefits

- IP40
- 5 year warranty

Optical Options

Code	Description
N/A	Opal

CCT Options

Code	Description
SWT	3000/4000/5000K Switchable

For 3000K version, replace '4K8' in part number with '3K8'

Control Options

Code	Description
/MW	Microwave sensor

For DALI control, replace 'F' in part number with 'D' for SwitchDim replace 'F' with 'S'. For corridor function, Microwave sensor or Nightlight add the code to the end.

Mounting Options

Code	Description
N/A	Surface

Finish Options

Code	Description
W	White (Standard)
PC	Polished Chrome
SC	Satin Chrome

Emergency Options

Code	Description
/EM	3 hour maintained, manual test

For emergency version, add onto end of part number as required.



HEAD OFFICE: Unit 4, Charlton Mead Lane, Hoddesdon, Hertfordshire EN11 0DJ

SHOWROOM: 121-131 Rosebery Ave, London EC1R 4RF

SHOWROOM: 1 New York St, Manchester M1 4HD

01992 445828



Enabled LED
Licensing Program for LED
Luminaires and Retrofit Bulbs

Member
Synergy Commercial
Lighting Limited

