

Polaris 10 Micro

Polaris 10 Micro LED Linear

LED Linear Luminaire







SPECIFICATION DATA							
Code	Finish	Diffuser	LED/m	Delivered Lumens (lm/m)	Total System Wattage (W/m)	Colour Temp (°K)	CRI
ТВС	Black	Opal	120	780	9.6	4000	>80
ТВС	Black	Opal	70	2100	15	4000	>80

- Part numbers are for individual luminaires.
- 5 year warranty
- See website for LDT files
- For CAD/BIM contact us
- For bespoke lengths please contact us
- See website for Technical Data Sheet
- IP40















Polaris 10 Micro LED Linear

LED Linear Luminaire



Construction

- Extruded aluminium profile
- · Clip-in diffuser
- European brand control gear

Optical Options

Code	Description
/OS	Opal (Standard)

Mounting Options

Code	Description
P1/SUS/1.25M	Suspended 1.25M
P1/SUS/3.0M	Suspended 3M
P1/SUS/5.0M	Suspended 5M
/NA	Surface Mounted (Standard)

For suspended specify the codes as required.

Features

- High efficiency LED boards
- Range of length options
- · Wide-beam light distribution

CCT Options

Code	Description
4K8	4000K (Standard)
3K8	3000K

For 3000K version, replace '4K8' in part number with

Applications

- Commercial and Business Areas
- Public buildings
- Housing
- Offices

Benefits

- Hotels and Restaurants
- Arts and Culture spaces

Custom-fit options

 Contemporary style • Energy efficient solution

• 5 Year warranty

Code	Description	
D	DALI	
S	Switchdim control	

For DALI control, replace 'F' in part number with 'D' for SwitchDim replace 'F' with 'S'

Control Options

Dimensions



Finish Options

Code	Description
В	Black RAL 9005 (Standard)
W	White RAL 9016
S	Anodised Aluminium
RAL	Any RAL by request
SFX	Special effect finishes (SFX) by request. See Product Portfolio

For White finish, replace 'B' in part number with 'W' for Silver replace 'B' with 'S'. Contact us for custom RAL and SFX finish prices

Continuous Options

Code	Description
С	Continuous
S	Start of run
E	End of run

Part numbers are for individual luminaires. For continuous replace 'I' in part number with 'C', 'S' or 'E'. Please sepcify continuous seperately.

ie P1CB/OS/F/3990/4K8

Please note, The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person.



HEAD OFFICE: Unit 4, Charlton Mead Lane, Hoddesdon, Hertfordshire EN11 0DJ SHOWROOM: 121-131 Rosebery Ave, London EC1R 4RF

SHOWROOM: 1 New York St, Manchester M1 4HD

01992 445828



Polaris 52 Direct Low Glare

LED Linear Luminaire



STANDARD FINISHES



Black finish as standard - respresented by 'B' in the part number





For White finish, replace 'B' in part number with 'W'



For Silver finish, replace 'B' in part number with 'S'

ANY RAL BY REQUEST







Contact us for custom RAL finishes prices and specification. Synergy Creativ can powder coat fittings to any RAL colour you require by request.

SPECIAL FX FINISHES







Contact us for all SFX finish prices and specification. Synergy Creativ's Special FX tetxured finished included Marble, Concrete, Wood Grains, Metallic and many more. all images are for illustrative purposes only actual product may vary, please contact us for samples.






Synergy Creativ also offers **Polaris 52 Direct Visual Comfort** version that meets standard EN 12464 which defines a maximum luminance limit of 3000 candelas per square metre at angles of 65 degrees and above.


Polaris 52 Direct Low Glare


LED Linear Luminaire

SWELTO


Accessories








X connector





T connector



HEAD OFFICE: Unit 4, Charlton Mead Lane, Hoddesdon, Hertfordshire EN11 0DJ

SHOWROOM: 121-131 Rosebery Ave, London EC1R 4RF

SHOWROOM: 1 New York St, Manchester M1 4HD



EnabLED Licensing Program for LED Luminaires and Retrofit Bulbs

Member Synergy Commercial Lighting Limited

