

# Venus

## Slim LED Bulkhead Luminaire

# SVIELTO



IP54

### SPECIFICATION DATA

Code	Finish	Size (mm)	Delivered Lumens (lm)	Total System Wattage (W)	Efficacy (lm/cw)	Colour Temp (°K)	CRI
<b>VNSW/R/F/1200/4K8</b>	Round, White	ø200 x 48	1247	12	103.9	4000K	>80
<b>VNSW/R/F/1800/4K8</b>	Round, White	ø300 x 40	1790	17.6	101.7	4000K	>80
<b>VNSW/R/F/2300/4K8</b>	Round, White	ø300 x 40	2365	24.5	96.5	4000K	>80
<b>VNSW/R/F/2900/4K8</b>	Round, White	ø400 x 40	2860	29	98.6	4000K	>80
<b>VNSW/S/F/1200/4K8</b>	Square, White	250x250x50	1195	12	99.6	4000K	>80
<b>VNSW/S/F/1600/4K8</b>	Square, White	300x300x50	1559	17.7	88.1	4000K	>80
<b>VNSW/S/F/3000/4K8</b>	Square, White	400x400x50	3028	28.3	107.0	4000K	>80

- 5 year warranty
- See website for LDT files
- For CAD/BIM contact us
- For bespoke lengths please contact us
- See website for Technical Data Sheet
- IP54



# Venus

## Slim LED Bulkhead Luminaire



### Construction

- Polycarbonate base and cover
- Opal diffuser

### Features

- Slim profile
- Beam angle 120 °
- Dimmable as standard

### Applications

- Offices
- Public spaces
- Hospitals
- Stairwells
- Corridors
- Schools

### Benefits

- IP54
- 3 year warranty
- Ultra Slim

### Optical Options

Code	Description
N/A	Opal

### CCT Options

Code	Description
4K8	4000K (Standard)
3K8	3000K

For 3000K version, replace '4K8' in part number with '3K8'

### Mounting Options

Code	Description
N/A	Surface

### Emergency Options

Code	Description
/EM	3 hour maintained, manual test
/ED	3 hour maintained, DALI / Self Test

For emergency version, add onto end of part number as required.



HEAD OFFICE: Unit 4, Charlton Mead Lane, Hoddesdon, Hertfordshire EN11 0DJ

SHOWROOM: 121-131 Rosebery Ave, London EC1R 4RF

SHOWROOM: 1 New York St, Manchester M1 4HD

01992 445828

