

TARX

LED DOWNLIGHT

TO ACCOMPANY TARX SPECIFICATION SHEETS



| Code | Cut Out Size | IP Rating Front / Rear | MacAdam (SDCM) | Power Factor | No. of drivers | Inrush Current (per driver) | Nominal Weight (Kg) | Rated Life | Mains Voltage (V) | Mains Frequency (Hz) |
|----------------|--------------|------------------------|----------------|--------------|----------------|-----------------------------|---------------------|---------------------|-------------------|----------------------|
| TRX/F/1100/3K8 | 176mm dia | IP20 / IP20 | 3 | >0.85 | 1 | 8A / 100uS | 6 | >60,000 hrs L80/B10 | 220-240 | 50-60 |
| TRX/F/1100/4K8 | 176mm dia | IP20 / IP20 | 3 | >0.85 | 1 | 8A / 100uS | 6 | >60,000 hrs L80/B10 | 220-240 | 50-60 |
| TRX/F/2000/3K8 | 176mm dia | IP20 / IP20 | 3 | >0.85 | 1 | 8A / 100uS | 6 | >60,000 hrs L80/B10 | 220-240 | 50-60 |
| TRX/F/2000/4K8 | 176mm dia | IP20 / IP20 | 3 | >0.85 | 1 | 8A / 100uS | 6 | >60,000 hrs L80/B10 | 220-240 | 50-60 |
| TRX/F/3000/3K8 | 176mm dia | IP20 / IP20 | 3 | >0.85 | 1 | 8A / 100uS | 6 | >60,000 hrs L80/B10 | 220-240 | 50-60 |
| TRX/F/3000/4K8 | 176mm dia | IP20 / IP20 | 3 | >0.85 | 1 | 8A / 100uS | 6 | >60,000 hrs L80/B10 | 220-240 | 50-60 |



Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25 °C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/- 10%. Synergy reserve the right to amend or change details without prior notification.

REVISED :17 August 2022 1