


# VENUS

## SLIMLINE LED BULKHEAD

TO ACCOMPANY VENUS SPECIFICATION SHEET



Code	Fixing Detail	IP Rating Front / Rear	MacAdam (SDCM)	Power Factor	No. of drivers	Inrush Current (per driver)	Nominal Weight (Kg)	Rated Life	Mains Voltage (V)	Mains Frequency (Hz)
VNSW/R/F/1200/4K8	2 @ 80mm centres	IP54	< 6	0.9	1	3.2A	0.4	40,000hrs L70/B50	220-240	50-60
VNSW/R/F/1800/4K8	2 @ 80mm centres	IP54	< 6	0.9	1	8.08A	0.85	40,000hrs L70/B50	220-240	50-60
VNSW/R/F/2300/4K8	2 @ 80mm centres	IP54	< 6	0.9	1	10.6A	0.95	40,000hrs L70/B50	220-240	50-60
VNSW/R/F/2900/4K8	2 @ 80mm centres	IP54	< 6	0.9	1	10.6A	1.4	40,000hrs L70/B50	220-240	50-60
VNSW/S/F/1200/4K8	2 @ 80mm centres	IP54	< 6	0.9	1	3.2A	0.65	40,000hrs L70/B50	220-240	50-60
VNSW/S/F/1600/4K8	2 @ 80mm centres	IP54	< 6	0.9	1	8.08A	1	40,000hrs L70/B50	220-240	50-60
VNSW/S/F/3000/4K8	2 @ 80mm centres	IP54	< 6	0.9	1	10.6A	1.9	40,000hrs L70/B50	220-240	50-60



Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25 °C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/- 10%. Synergy reserve the right to amend or change details without prior notification.

REVISED :19 August 2022