

ARENDA

HEXAGONAL BIOPHILIC PENDANT

TO ACCOMPANY ARENDAL GRID, MESH, MOSS AND TROF SPECIFICATION SHEETS



Code	Fixing Detail	IP Rating Front / Rear	MacAdam (SDCM)	Power Factor	No. of drivers	Inrush Current (per driver)	Nominal Weight (Kg)	Rated Life	Mains Voltage (V)	Mains Frequency (Hz)
	See Drawing	IP40	3	0.95	1	33A / 250uS	8.1	>60,000 hrs L70 / B10	220-240	50-60
	See Drawing	IP40	3	0.95	1	51.5A / 157uS	9.7	>60,000 hrs L70 / B10	220-240	50-60
	See Drawing	IP40	3	0.95	2	51.5A / 157uS	11.2	>60,000 hrs L70 / B10	220-240	50-60
	See Drawing	IP40	3	0.95	2	51.5A / 157uS	14.6	>60,000 hrs L70 / B10	220-240	50-60
	See Drawing	IP40	3	0.95	1	33A / 250uS	8.1	>60,000 hrs L70 / B10	220-240	50-60
	See Drawing	IP40	3	0.95	1	51.5A / 157uS	9.7	>60,000 hrs L70 / B10	220-240	50-60
	See Drawing	IP40	3	0.95	2	51.5A / 157uS	11.2	>60,000 hrs L70 / B10	220-240	50-60
	See Drawing	IP40	3	0.95	2	51.5A / 157uS	14.6	>60,000 hrs L70 / B10	220-240	50-60

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25 °C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/- 10%. Synergy reserve the right to amend or change details without prior notification.

REVISED :6 October 2022

