


SYNERGY
CREATIV.




Tromsø
Oval - MESH

S+ STRØM +
OVERGAARD

Tromsø

Oval - MESH

S+ STRØM +
OVERGAARD



SPECIFICATION DATA

Code	Finish	Diffuser	Size (mm)	Delivered Lumens (lm)	Total System Wattage (W)	Efficacy (lm/cw)	Colour Temp (°K)	CRI
TRMM/AX/OS/F/4K/***	Black	Opal	700x1547	5796	54	107.3	4000	>80
TRMM/AY/OS/F/4K/***	Black	Opal	900x1747	6688	62	107.9	4000	>80
TRMM/AZ/OS/F/4K/***	Black	Opal	1200x2047	8025	74	108.4	4000	>80

- 5 year warranty
- See website for LDT files
- For CAD/BIM contact us
- See website for Technical Data Sheet
- IP20



TRIDONIC



Scenario
INTELLIGENT INFRASTRUCTURES



UK CA CE

Tromsø

Oval - MESH

Construction

- Aluminium
 - Opal Diffuser
-

Features

- LED
 - Stylish Design
 - Besoke Options
-

Applications

- Commercial and Business Areas
 - Public Buildings
 - Retail
 - Offices
 - Hotels and Restaurants
 - Arts and Culture spaces
-

Benefits

- Contemporary Style
 - Energy Efficient Solution
 - 5 Year Warranty
-

Optical Options

Code	Description
/OS	Opal (Standard)
/HXP	Low Glare

CCT Options

Code	Description
3K8	3000K
4K8	4000K

Mounting Options

Code	Description
	Suspended (Standard)
	Surface

Finish Options

Code	Description
B	Black
W	White
G	Grey
RAL	Any RAL by request

Please note, The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person.

Tromsø

Oval - RANGE


S+ STRØM +
OVERGAARD



Oval - GRID



Oval - MESH



Oval - MOSS



SHOWROOM: 121-131 Rosebery Ave, London EC1R 4RF

SHOWROOM: 1 New York St, Manchester M1 4HD

01992 445828



EnabLED
Licensing Program for LED
Luminaires and Retrofit Bulbs

Member
Synergy Commercial
Lighting Limited

