

TROMSØ

OVAL BIOPHILIC PENDANT

TO ACCOMPANY TROMSØ GRID, MESH AND MOSS SPECIFICATION SHEETS



Code	Fixing Detail	IP Rating Front / Rear	MacAdam (SDCM)	Power Factor	No. of drivers	Inrush Current (per driver)	Nominal Weight (Kg)	Rated Life	Mains Voltage (V)	Mains Frequency (Hz)
TBC	See Drawing	IP20	3					>50,000 hrs L70 / B10	220-240	50-60
TBC	See Drawing	IP20	3					>50,000 hrs L70 / B10	220-240	50-60
TBC	See Drawing	IP20	3					>50,000 hrs L70 / B10	220-240	50-60
TBC	See Drawing	IP20	3					>50,000 hrs L70 / B10	220-240	50-60
TBC	See Drawing	IP20	3					>50,000 hrs L70 / B10	220-240	50-60
TBC	See Drawing	IP20	3					>50,000 hrs L70 / B10	220-240	50-60
TBC	See Drawing	IP20	3					>50,000 hrs L70 / B10	220-240	50-60
TBC	See Drawing	IP20	3					>50,000 hrs L70 / B10	220-240	50-60
TBC	See Drawing	IP20	3					>50,000 hrs L70 / B10	220-240	50-60
TBC	See Drawing	IP20	3					>50,000 hrs L70 / B10	220-240	50-60



Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25 °C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/- 10%. Synergy reserve the right to amend or change details without prior notification.

REVISED :6 October 2022