Lega 25 Magnetic Track Pendant

Magnetic Track Lighting







SPECIFICATION DATA	ECIFICATION DATA							
Code	Finish	Diffuser	Size (mm)	Delivered Lumens (lm)	Total System Wattage (W)	Efficacy (Ilm/cw)	Colour Temp (°K)	CRI
ТВС	Black	LED lens	ø30 x 45	210	1.5	140	2700	>80
ТВС	Black	LED lens	ø30 x 45	215	1.5	143.3	3000	>80
ТВС	Black	LED lens	ø30 x 45	230	1.5	153.3	4000	>80

COMPATIBLE WITH















Lega 25 Magnetic Track Pendant

Magnetic Track Lighting



Construction

- Cast-pressed aluminium
- LED lens
- Requires 48V DC Track

Optical Options

Code	Description	
	LED lens	

Mounting Options

Code	Description		
T1	Low voltage standard track		
T2	Low voltage track double emission		
T5	Low voltage trimless track		
T8	Low voltage recessed track		

Features

- Vertical 90° / Horizontal 360°
- Remote electronic transformer
- IP20

CCT Options

Code	Description	
4K8	4000K	
3K8	3000K	

Finish Options

Code	Description		
В	Black (Standard)		
W	White		
GL	Gold		


Applications

- Commercial and Business Areas
- Public buildings
- Co-work spaces
- Offices
- Hotels and Restaurants
- Arts and Culture spaces

Benefits

- Contemporary style
- Energy efficient solution
- Compact mini spotlight

Dimensions



Please note, The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person.



HEAD OFFICE: Unit 4, Charlton Mead Lane, Hoddesdon, Hertfordshire EN11 0DJ SHOWROOM: 121-131 Rosebery Ave, London EC1R 4RF SHOWROOM: 1 New York St, Manchester M1 4HD



EnabLED Licensing Program for LED Luminaires and Retrofit Bulbs

Synergy Commerci Lighting Limited



Lega 25 Magnetic Track Pendant

Magnetic Track Lighting Acessories



