









SPECIFICATION DATA								
Code	Finish	Beam Angle (°)	Size (mm)	Delivered Lumens (lm)	Total System Wattage (W)	Efficacy (Ilm/cw)	Colour Temp (°K)	CRI
DOL08B/D/2000	Black	54	80 ø x 172	2000	15	133	4000K	90

Code Description

DOL08-10B/SUSKIT Separate 1.5m suspension kit for direct or suspension from a BESA box

- 5 year warranty
- See website for LDT files
- For CAD/BIM contact us
- For bespoke lengths please contact us
- See website for Technical Data Sheet
- IP20
- BESA Box Mountable
- Suspension kit with matching rose availiable

















Commercial Surface, Suspended or BESA Mounted Downlight



Construction

- Extruded aluminium and steal
- Multi-faceted 54° reflector
- Built in driver

Optical Options

Code	Description	
N/A	Multi-faceted 16° reflector	
N/A	Multi-faceted 24/36° reflector	
N/A	Multi-faceted 54° reflector	

Mounting Options

Code	Description		
N/A	Surface or BESA Mounted		
N/A	1.5m Suspended ceiling or BESA		

Suspension kit to be ordered separately

Features

- Besa mountable
- Ideal for ceilings without a void
- IP20

CCT Options

Code	Description	
4K8	4000K (Standard)	
3K8	3000K	

For 3000K version, replace '4K8' in part number with '3K8'

Finish Options

Code	Description	
В	Black (Standard)	
W	White	
G	Grey	

For White finish, replace 'B' in part number with 'W' for Grey replace 'B' with 'G'

Applications

- Commercial and Business Areas
- Public buildings
- Co-work spaces
- Offices
- Hotels and Restaurants
- Arts and Culture spaces

Control Options

Code	Description		
D	DALI (Standard)		
	Brief (Staridard)		


Switchdim or fixed output can be wired on site

Benefits

- Contemporary style
- Energy efficient solution
- Tridonic control gear



Dimensions





HEAD OFFICE: Unit 4, Charlton Mead Lane, Hoddesdon, Hertfordshire EN11 0DJ SHOWROOM: 121-131 Rosebery Ave, London EC1R 4RF

SHOWROOM: 1 New York St, Manchester M1 4HD

01992 445828

